





Green Pin Super® Bow Shackle SC

Grade 8 bow shackle with screw pin



G-5261



- **Material:** bow and pin alloy steel, grade 8, quenched and tempered
- **Safety Factor:** MBL equals 5 x WLL
- **Standard:** ASME B30.26 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVA Class 2, grade B
- **Finish:** hot dipped galvanized
- **Temperature Range:** -20 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^{*} CE IIA ABS PDA^{*} ABS MA^{*}
- **Article code:** scan QR code to see article codes

working load limit	diameter body	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
3.3	13.5	16	34	13	22	51	32	90	73	59	0.36
5	16	19	40	16	27	64	43	110	89	75	0.63
7	19	22	46	19	31	76	51	129	103	89	1.01
9.5	22	25	52	22	36	83	58	144	119	102	1.50
12.5	25	28	59	25	43	95	68	164	137	118	2.21
15	28	32	67	28	47	108	75	186	153	131	3.16
18	32	35	73	32	51	115	83	201	170	147	4.31
21	35	38	79	35	57	133	92	227	186	162	5.58
30	38	42	88	38	60	146	99	249	203	175	7.43
40	45	50	104	45	74	178	126	300	243	216	12.5
55	57	57	119	57	83	197	138	341	286	252	17.2
85*	70	70	145	70	105	260	180	437	354	320	37.6

CAD RFID INFO



* Excluded from ABS Type Approval